Terranova – Slackline – Product Specification



Terranova - Elements for Low Ropes Courses

Low Ropes Courses are not so much about the thrills of individual sport, but about psychomotor learning and about teamwork in group initiatives. All that happens in a low-risk environment. The importance of positive social behavior and the ability to communicate can be experienced and the ability for risk assessment is getting playfully improved.

Terranova – Slackline – at a glance.

Product Family:

ltem Number: Children's Age: Fall Height (DIN EN 1176): Length x Width x Height:

Protective Surfacing Area (DIN EN 1176): Protective Surfacing Area (ASTM 1487):

Minimum space required DIN EN 1176: Minimum space required ASTM 1487: Elements for Low Ropes Courses 96.180.031 5+ 0.60 m (2'-0") 6.55 m x 0.22 m x 1.8 m (21'-6" x 0'-9" x 5'-11") 9.50 m x 3.32 m 10.16 m x 3.88 m (33'-4" x 12'-9") 28.39 m² 36.19 m² (389.6 sf) Number of Foundations:

Concrete Volume C20/C25: Number of skilled installers required: Installation Time without foundation: Dimensions of largest part:

Weight of heaviest part: Shipping Volume:

Spare part guarantee: Certificate according to DIN EN 1176: 2 рс.

2.02 m³ (71.4 ft³) 2 3 hours Ø 0.133 x 2.8 m (5¼" x 9'-3") 65 kg (143.3 lbs) 2.7 m³ (95.4 ft³)

Lifelong No.: Z2.16.01.10256.255 TÜV Product Service




Berliner Seilfabrik Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178

www.berliner-playequipment.com info@berliner-seilfabrik.com







Terranova posts:

Terranos[®] steel posts are bent in a little bow (r=9000 mm) with individual round cast aluminum post tops and Terranos-clamps with Chrox-connectors; Ø 133 mm (5 ¼''); wall thickness 7.1 mm (1/4''); anti-corrosion treatment and color finish: sandblasting and solvent-free zinc-/ epoxy-/ polyester-process

Connections:

U-Rope®- TERRANOS® aluminum clamps with ChroX connection on post with infinitely adjustable height and device / adjustable in position, ChroX aluminum connection for fixing the stainless steel chains. All aluminum connectors anticorrosive sandblasted and solvents in epoxy / polyester / burn-colored powder coating. Stainless steel chain fixed by aluminum ferrules on all rope ends fixed for connection to the ChroX connection

Rope:

U-Rope®-round strand ropes with galvanized and covered wires: external strands with non-abrasive UV-resistant Polyester-yarn (no Polypropylene); rope-diameter Ø 16 mm (5/8")



Play Equipment Corporation 96 Brookfield Oaks Drive, Suite 140 Greenville, SC 29607

T + 1 864 627 1092 F + 1 864 627 1178

www.berliner-playequipment.com info@berliner-seilfabrik.com

